

TECHNICAL DATA SHEET

HYDRAULIC JACK OIL



DESCRIPTION

Hydraulic Jack Oil is suitable for use in standard hydraulic, jack and hoist systems. It is also suitable for use in systems that use vane, piston or gear pumps, and vacuum pumps.

SUMMARY OF BENEFITS

- Improved equipment life and decreased downtime due to superior wear and corrosion protection
- Enhanced chemical and thermal stability provide long fluid life and permit higher operating temperatures
- Excellent air release and antifoam properties to prevent cavitation and oxidation
- Excellent filterability even when contaminated, thereby preventing filter blockages. This saves filter replacement costs and down time
- Enhanced low frictional characteristics to prevent the occurrence of "stick slip"

COMPATIBILITY

Hydraulic Jack Oil is compatible with most pumps, valves, and seal materials. However, like all hydraulic oils containing zinc anti wear additives, it is not suitable for use with pumps having silver plated parts (e.g. some Lucas units). Contamination of Jack oil with other oils, especially engine oils, must be avoided as it can form gels which impair air release, anti foaming and demulsibility of the fluid.

SUITABLE FOR



SPECIFICATIONS

- ISO VISCOSITY GRADE 32
- CINCINNATI MILACRON P68, P69, P70
- DENISON HF-0, HF-1, HF-2
- DIN 51 524 PART 2 (HLP TYPE OILS)
- US STEEL 136, 127
- VICKERS 1-286-S, M2952-S

MEETS THE REQUIREMENTS OF THE FOLLOWING PUMP MANUFACTURERS:

- HAGGLUND
- REXROTH
- DANFOSS
- LINDE
- BOSCH
- RACINE
- CINCINNATI MILACRON
- SUNSTRAND
- DENISON
- OILGEAR
- COMMERCIAL HYDRAULICS
- VICKERS

HYDRAULIC JACK OIL	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.865
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	32
@ 100°C	ASTM D445	cSt	4.3
VISCOSITY INDEX	ASTM D2270	-	4.3
POUR POINT	ASTM D97	°C	-27
FLASH POINT (COC)	ASTM D92	°C	>224

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

1LT - #30194

February 2022

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
 Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au