

DESCRIPTION

SYN-X COMPLY 5W-30 is a specially engineered high performance synthetic lubricant suitable for many late model passenger vehicles, 4WD, SUV and Utilities fuelled by gasoline, whether naturally aspirated or turbo charged. Formulated to exceed the latest API SP and ILSAC GF-6A performance levels to protect against low speed pre-ignition (LSPI), timing chain wear, deposit formation and oxidative thickening which can plague modern engine designs. SYN-X COMPLY 5W-30 offers enhanced fuel economy and uncompromising engine protection in today's stop-start driving conditions.

SUMMARY OF BENEFITS

- Synthetic formulation offering enhanced temperature-viscosity characteristics for better cold flow whilst maintaining operating temperature protection
- Enhanced oxidation stability allows longer oil drain intervals
- Excellent control of combustion components resulting in cleaner engines
- 5W-30 viscosity offers excellent fuel economy whilst maintaining high level engine protection
- API SP and ILSAC GF-6A is backwards compatible with earlier performance levels to help minimize the number of required fluids

SPECIFICATIONS

- SAE 5W-30
- API SP
- ILSAC GF-6A

SYN-X COMPLY 5W-30	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.855
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	62.5
@ 100°C	ASTM D445	cSt	10.4
VISCOSITY INDEX	ASTM D2270	-	156
POUR POINT	ASTM D97	°C	-39
FLASH POINT (COC)	ASTM D92	°C	200
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	7.5
SULPHATED ASH	ASTM D874	% mass	0.8

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

#300386