

**DESCRIPTION**

Pro Series Euro 5W-30 is a synthetic high performance diesel and petrol engine oil suitable for late model passenger motor vehicles including those fitted with particulate filters. Pro Series Euro 5W-30 meets and complies with the demanding requirements of Euro 5 & 6 exhaust emission legislation. Formulated to meet API SP requirements, Pro Series Euro 5W-30 is ideally designed for European vehicles calling for the ACEA C2/C3 specification such as VW, BMW and other European vehicles. Also meets BMW long-life LL-04, Mercedes-Benz 229.51 specifications. Upgraded formulation protects turbo charged gasoline direct injection engines against Low Speed Pre-Ignition (LSPI).

**SUMMARY OF BENEFITS**

- Low SAPS (Sulfated Ash, Phosphorus and Sulfur)
- Super extended drain intervals surpassing any mineral or American diesel type lubricant
- Excellent soot and sludge control resulting in cleaner engines
- Reduces fuel consumption due to superior technology
- Outstanding low temperature viscometrics for reduced wear at start up
- Excellent mixed fleet oil
- Suitable for European, American and Japanese diesel engines
- LSPI protection for the latest turbo engines
- Fuel efficient ACEA C2 with ACEA C3 level of protection

**SPECIFICATIONS**

- ACEA C2/C3
- API SP
- MB-APPROVAL 229.31/229.51
- MB-APPROVAL 226.5
- VW 502 00/505 01
- BMW LONGLIFE - 04
- GM DX2
- PORSCHE A40
- RENAULT RN0700/RN0710

**SUITABLE FOR**



PRO SERIES EURO 5W-30	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.850
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	69
@ 100°C	ASTM D445	cSt	11.6
VISCOSITY INDEX	ASTM D2270	-	162
POUR POINT	ASTM D97	°C	-36
FLASH POINT (COC)	ASTM D92	°C	210
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	7.9
SULPHATED ASH	ASTM D874	% mass	<0.80

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

200LT - #300206PRO

September 2023